

Technical specification sheet

06 S 6 SD | Vari Pump

Specifications			
article number			100.152.012
model			06 S 6 SD
max. working pressure	psi		10443
short description			Vari Pump
capacity oil tank (effective)	oz		202.9
number of outputs			1
number of stages			1
first stage output / min.	oz		20.3
first stage pressure range	psi		0 - 10443
operator type			electric motor
engine			230 VAC - 1.1 kW - 50 Hz - 1 Ph
speed	rpm		1450
weight, ready for use	lb		79.4
dimensions (LxWxH)	in		15.7 x 11.8 x 16.2

Accessories	
Connecting Block M 301 B	100.182.088
SADA Power Switch M304	100.172.051
Pressure Control Valve M 303	100.181.303
Valve, Double Acting M 326	100.182.321
Valve, Double Acting M 322	100.181.322
Protection Frame	100.151.056
Valve, Double Acting M 323	100.181.323
Cover Plate	100.151.040
Carrying Handle Set	100.151.053
Connecting Plate M 302	100.181.302
Valve, Single Acting M 311	100.181.311



holmatro.com

© Holmatro 2021-09-11

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.