

## Technical specification sheet

# 12 W 6 SD | Vari Pump

Specifications		
article number		100.152.033
model		12 W 6 SD
max. working pressure	psi	10443
short description		Vari Pump
capacity oil tank (effective)	oz	202.9
number of outputs		1
number of stages		2
first stage output / min.	oz	108.2
second stage output / min.	oz	40.6
first stage pressure range	psi	0 - 2901
second stage pressure range	psi	2901 - 10443
operator type		electric motor
engine		230 VAC - 1.5 kW - 50 Hz - 1 Ph
speed	rpm	2850
weight, ready for use	lb	88.2
dimensions (LxWxH)	in	15.7 x 11.8 x 17.4

Accessories		
Connecting Block M 301 B		100.182.088
SADA Power Switch M304		100.172.051
Pressure Control Valve M 303		100.181.303
Valve, Double Acting M 326		100.182.321
Valve, Double Acting M 322		100.181.322
Protection Frame		100.151.056
Valve, Double Acting M 323		100.181.323
Cover Plate		100.151.040
Carrying Handle Set		100.151.053
Connecting Plate M 302		100.181.302
Valve, Single Acting M 311		100.181.311



[holmatro.com](http://holmatro.com)

© Holmatro 2021-09-11

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.