
Technical specification sheet

HAHC20S20 | Aluminum Hollow Plunger Cylinder

| Specifications | | | |
|----------------------------------|-----------------|-------------------------------------|--|
| article number | | 100.112.369 | |
| short description | | Aluminum Hollow Plunger Cylinder | |
| model | | HAHC20S20 | |
| max. working pressure | bar/Mpa | 720 / 72 | |
| tonnage | t | 20 | |
| stroke | mm | 200 | |
| closed height | mm | 375 | |
| capacity | kN/t | 208 / 21.2 | |
| effective pressure area | cm ² | 28.9 | |
| required oil content (effective) | CC | 577 | |
| connection | | A 118 | |
| cylinder type | | hollow plunger | |
| acting type | | single | |
| return type | | spring | |
| material | | aluminium | |
| weight, ready for use | kg | 6.3 | |
| ASME | | B30.1 | |





| Technical drawing dimensions | | |
|------------------------------|----|------|
| dimension A | mm | 375 |
| dimension B | mm | 98 |
| dimension C | mm | 63 |
| dimension D | mm | 80 |
| dimension E | mm | 24.5 |
| dimension F | mm | 296 |
| dimension G | mm | 43.5 |
| dimension H | mm | 150 |
| dimension R | mm | 27 |
| angle A1 | 0 | 45 |

Standard supplied with

High Flow female coupler A 118Hollow saddle

| Accessories | |
|--------------|-------------|
| Saddle TRS20 | 100.003.650 |

holmatro.com

© Holmatro 2021-09-10

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T+31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.

