
Technical specification sheet

HAHC30S20 Aluminum Hollow Plunger Cylinder

Specifications			
article number		100.112.374	
short description		Aluminum Hollow Plunger Cylinder	
model		HAHC30S20	
max. working pressure	bar/Mpa	720 / 72	
tonnage	t	30	
stroke	mm	200	
closed height	mm	390	
capacity	kN/t	343 / 35	
effective pressure area	Cm ²	47.7	
required oil content (effective)	CC	954	
connection		A 118	
cylinder type		hollow plunger	
acting type		single	
return type		spring	
material		aluminium	
weight, ready for use	kg	11.1	
ASME		B30.1	





Technical drawing dimensions		
dimension A	mm	390
dimension B	mm	126
dimension C	mm	83
dimension D	mm	80
dimension E	mm	33
dimension F	mm	312
dimension G	mm	43.5
dimension H	mm	150
dimension R	mm	34
angle A1	0	45

Standard supplied with

High Flow female coupler A 118Hollow saddle

Accessories	
Saddle TRS30	100.003.654

holmatro.com

© Holmatro 2021-09-10

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T+31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.

