

Technical specification sheet

HHJ 30 H 15 | Hollow Plunger Cylinder

Specifications		
article number		100.122.045
short description		Hollow Plunger Cylinder
model		HHJ 30 H 15
max. working pressure	psi	10443
tonnage	lb	66139.0
stroke	in	5.9
closed height	in	11.2
capacity (press)	lbf	66026
capacity (retract)	lbf	29450
effective pressure area (press)	sq. in.	6.3
effective pressure area (retract)	sq. in.	2.8
required oil content (press)	oz	20.7
required oil content (retract)	oz	9.3
connection		A 118
cylinder type		hollow plunger
acting type		double
return type		hydraulic
material		steel
weight, ready for use	lb	50.7

Technical drawing dimensions		
dimension A	in	11.2
dimension B	in	4.7
dimension C	in	2.8
dimension D1	in	2.8
dimension D2	in	3.3
dimension E	in	1.6
dimension F	in	10.8
dimension P	in	2
dimension R	in	1.3
dimension S	threadsize	M50x1,5
I type		[I2]

Standard supplied with	
• High Flow female coupler A 118 on inlet port	
• High Flow female coupler with pressure relief valve A 418 on outlet port	
• Hollow saddle	

Accessories	
Flat Saddle S 35 B	100.181.015
Thread Saddle S 35 C	100.181.016

