

Technical specification sheet


HJ 50 H 15 | Cylinder

Specifications		
article number		100.122.002
short description		Cylinder
model		HJ 50 H 15
max. working pressure	bar/Mpa	720 / 72
tonnage	t	50
stroke	mm	150
closed height	mm	282
capacity	kN/t	510.3 / 52
effective pressure area (press)	cm ²	70.9
effective pressure area (retract)	cm ²	20.6
required oil content (press)	cc	1064
required oil content (retract)	cc	309
connection		A 118
cylinder type		high tonnage
acting type		double
return type		hydraulic
material		steel
weight, ready for use	kg	27.0

Technical drawing dimensions		
dimension A	mm	282
dimension B	mm	130
dimension C	mm	80
dimension D1	mm	70
dimension D2	mm	85
dimension E	mm	25
dimension F	mm	275
dimension P	mm	70
I type		[I2]

Standard supplied with	
• High Flow female coupler A 118	
• Flat saddle	

Accessories	
Tilting Saddle S 50 TN	100.181.043



holmatro.com

© Holmatro 2021-09-11

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.